

# AXIS Random Selector

## Smart analytics for unbiased inspection

AXIS Random Selector is a proven camera-integrated video analytics application for randomly singling out individuals for inspection. The application eliminates any bias in the selection and inspection of, for instance, employees leaving a store, and may thereby reduce employees' discomfort. The application comes with the AXIS People Counter functionality, which collects data such as how many people have entered or left, and at what times. AXIS Random Selector stores data directly in each camera for easy access through the camera's web interface or for export. Data can also be accessed via AXIS Store Reporter.

- > **Real-time random selection and inspection of people**
- > **Loss prevention**
- > **Based on proven technology**



# AXIS Random Selector

Application		System integration	
<b>Supported products</b>	For a complete list of recommended and supported products, go to <a href="http://www.axis.com">www.axis.com</a>	<b>Application Programming Interface</b>	Open API for software integration. Specifications available at <a href="http://www.axis.com">www.axis.com</a>
<b>Functionality</b>	Automatic upload to separately sold AXIS Store Data Manager and AXIS Store Reporter. Statistical data stored up to 90 days without SD card. AXIS People Counter functionality.	<b>Event integration</b>	Integrates with camera event management system to enable event streaming to Video Management Software and camera actions such as I/O control, notification, and edge storage.
<b>Configuration</b>	Web configuration interface included	<b>General</b>	
<b>Licenses</b>	Demo license available at <a href="http://www.axis.com">www.axis.com</a>	<b>Languages</b>	English, German, Spanish, Italian, French, Chinese (simplified), Japanese, Russian
<b>Scenarios</b>		Environmental responsibility: <a href="http://www.axis.com/environmental-responsibility">www.axis.com/environmental-responsibility</a>	
<b>Typical applications</b>	Retail environments to prevent internal theft by selecting employees randomly for inspection.		
<b>Mounting height</b>	2.7 m to 10 m (8 ft 10 in to 32 ft 10 in)		
<b>Limitations</b>	Objects below approximately 110 cm (43 in) are not counted.		