

## AXIS W703 Docking Station 8-bay

AXIS W703 Docking Station 8-bay enables easy handling of the body worn cameras with fast charging, quick, secure and easy data offloading.

- > **Grab and go, ready when you are**
- > **Dock and go, for automatic reliable offloading and fast charging**
- > **Reliable docking connectors**
- > **Splash proof**



## AXIS W703 Docking Station 8-bay

<b>Network</b>		<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 10-85% RH (non-condensing)
<b>Network protocols</b>	IPv4, IPv6 USGv6, HTTPS, Bonjour, DNS, NTP, TCP, UDP, ICMP, DHCP, ARP	<b>Approvals</b>	EMC EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), RCM AS/NZS CISPR 32 Class A
<b>Throughput</b>	100 Mbit/s (per camera)	<b>Safety</b>	IEC/EN/UL 62368-1
<b>General</b>		<b>Environment</b>	IEC 60068-2-1, IEC 60068-2-14, IEC 60068-2-2, IEC 60068-2-78
<b>Capacity</b>	8 bays	<b>Network</b>	Compatible with NIST SP500-267 throughput
<b>Casing</b>	Plastic casing Color: black NCS S 9000-N	<b>Dimensions</b>	Height: 52 mm (2.1 in) Width: 128 mm (5.1 in) Depth: 425 mm (16.8 in)
<b>Mounting</b>	Screws (included)	<b>Weight</b>	800 g (1.76 lb)
<b>Sustainability</b>	PVC free	<b>Warranty</b>	3-year warranty, see <a href="https://www.axis.com/warranty">axis.com/warranty</a>
<b>Power</b>	11.4–12.6 V DC, max 80 W		
<b>Connectors</b>	Shielded RJ45 10BASE-T/100BASE-TX/1000BASE-T DC input Pogo pin pads		
<b>Operating conditions</b>	0 °C to 40 °C (32 °F to 104 °F) Humidity 10–85% RH (non-condensing)		